



Instantly efficient, instantly sustainable

Philips MASTER LEDtube
Value InstantFit

PHILIPS

The first hassle-free retrofit LED solution that works with electronic ballast

LED is rapidly replacing fluorescent tubes as a more sustainable light source – but none faster than Philips MASTER LEDtube Value InstantFit. Designed by the market-leading experts in LED, MASTER LEDtube Value InstantFit integrates a LED light source into a traditional tube form that's quick, easy and safe to install.

The world's first LED replacement tube that requires no rewiring, InstantFit is compatible with HF fixtures and drivers in linear fluorescent tube lighting. A simple switch

that reduces the time it takes to replace fluorescent with LED to just a couple of minutes per fixture.

MASTER LEDtube Value InstantFit can reduce power consumption by up to 50% compared to linear fluorescent tube lighting. Thanks to their long lifetime they also extend the replacement cycle and require less maintenance. Add to that the low cost of installation and the return on investment is just 1-3 years. A world's first that's sure to be an instant hit for you and your customers.



What is InstantFit?

A plug and play solution that works straight out of the box

No hassle changing drivers

No expensive rewiring, low installation costs

Benefits

Instant energy savings of up to 50%

Long reliable lifetime of up to 40,000 hours

CE certified





Why Philips for LEDtubes?

Innovation leader in linear lighting

Philips has a long history of ground-breaking innovation with LED integration delivering 200 lm/W, and added integrated intelligence, as the latest additions.

Real quality of light

Philips' products deliver claimed specifications, come with all required certifications, and are compliant with the latest regulation.

Lighting expertise

Philips has a proven track record of reliable LEDtube projects in challenging and safety-critical environments, such as underground metro systems and frozen-food storage spaces.

Multiple offerings

Philips offers multiple LEDtubes to serve different customer needs.

Check the full story and complete MASTER LEDtube range on www.philips.com/masterledlamps

Product specifications



Non-Dimmable

Beam angle

G13

MASTER LEDtube	Product	Color temp (K)	System wattage (W)	Lumen output (lm)	Efficacy (lm/W)	Lifetime (hrs)	Exit window	Cap base	CRI	Operation	EOC	12NC
Value	1200mm	4000	16	1600	100	40.000	140	G13	85	EM & Mains	871829173523600	929000285002
Value	1200mm	6500	16	1600	100	40.000	140	G13	85	EM & Mains	871829173525000	929000285102
Value InstantFit	1200mm	4000	16,5	1600	100	40.000	140	G13	85	HF	871829172885600	929000284402
Value InstantFit	1200mm	6500	16,5	1600	100	40.000	140	G13	85	HF	871829172887000	929000284502



See for more information www.philips.com/instantfit



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Document order number: 0000 000 00000